

# RILSAN® PA11 SPIRAL HOSES

| DIMENSIONS |     | SPIRALS LENGHT / MT. |                 |                | DIAMETERS        |
|------------|-----|----------------------|-----------------|----------------|------------------|
| o Ø        | i Ø | LINEAR HOSES MT.     | OUT OF WORK MT. | WORKING LENGHT | INSIDE / OUTSIDE |
| 4          | 2   | 10                   | 0,460           | 6,50           | 20-28            |
| 4          | 2   | 10                   | 0,400           | 6,50           | 30-38            |
| 4          | 2,5 | 10                   | 0,460           | 6,50           | 20-28            |
| 4          | 2,5 | 10                   | 0,400           | 6,50           | 30-38            |
| 6          | 4   | 25                   | 0,870           | 16             | 50-60            |
| 6          | 4   | 30                   | 0,950           | 20             | 55-67            |
| 8          | 6   | 25                   | 1,000           | 16             | 60-76            |
| 8          | 6   | 30                   | 1,000           | 20             | 70-86            |
| 10         | 8   | 25                   | 0,950           | 16             | 80-100           |
| 10         | 8   | 30                   | 1,000           | 20             | 90-110           |
| 12         | 10  | 30                   | 1,000           | 20             | 110-134          |
| 15         | 12  | 30                   | 0,920           | 20             | 150-180          |
| 16         | 12  | 30                   | 0,880           | 20             | 160-196          |
| 18         | 14  | 30                   | 0,970           | 20             | 160-196          |
| 18         | 15  | 30                   | 0,970           | 20             | 160-196          |
| 22         | 18  | 60                   | 0,980           | 40             | 400-444          |
| 24         | 20  | 25                   | 0,950           | 18             | 200-248          |
| 24         | 20  | 50                   | 0,980           | 35             | 400-448          |

## STANDARD COLOURS :

Blue, orange and on request red, yellow, green, black, neutral, light blue.

## TEMPERATURE °C :

For working pressures related to temperature, pls. see the table of LINEAR hoses.

To avoid any alteration we advise you to employ RILSAN spiral within -20° / +60°.

Our normal and spiral hoses in RILSAN® produced for cars, are according to the most known international regulations, such as : SAE - NF - DIN - BS - ISO.

We make spiral to design



The informations contained in this document are based on trials carried out by ARKEMA Research Center and data selected from the literature, may shall in no event be held to be constitute or imply any warranty, undertaking, express or implied committent from our part.